



Automatic Water Boiler

EB3FX/TT

- **Twin tank model**
- **Tanks can be set to different temperatures – ideal for brewing black teas at 98°C and green teas at 70°C**
- **Plus all the features of the EB3FX**



Water Boiler Features

- Lockable mode
- High quality filtered boiling water on tap 24 hours a day
- Precise electronic temperature control system
- Large, colour touchscreen display.
- Narrow 250mm width
- Energy saving eco mode
- Energy saving Intelligent predictive eco mode
- 7-day programmable timer to conserve energy
- Insulated tanks for minimal heat loss and energy conservation
- Built-in water filtration system improves water quality and reduces scale build-up
- High volume, easy change FilterFlow cartridge - removes sediment and impurities such as chlorine and reduces limescale build-up
- Adjustable water temperature - from 70°C - 98°C
- Screw cap and indicator probe to help you monitor limescale build up
- Descaling process with step-by-step instructions provided on screen*
- Enhanced multi-level diagnostics
- Designed for connection to a potable cold water supply
- Water and power supplies can be fed from the underside so no wires or pipes are visible
- WRAS approval pending

Cleaning and Servicing

- Easy clean stainless steel external finish and smooth black trim
- Easy clean removable drip tray
- Easy change filter cartridge
- Screw cap and indicator probe to monitor limescale build up
- Easy descale process
- Enhanced diagnostics, the on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

Overall Construction

- Long life incoloy elements
- Mirror finish stainless steel
- Smooth ABS/PC trim
- Two stainless steel water tanks
- 1.8 metres of cable and a 13 amp moulded plug on EB3FX

Inclusive Accessories

- Removable drip tray
- Water feed hose (1m)
- FC04 5,600 litre filter cartridge

*An engineer may still be required in hard water areas.

Available Options

- EB3FX Automatic water boiler
- EB3FX/PB Push button model

Available Accessories

- BR55 Wall mounting kit for EB3FX and EB4FX models
- FC04 5,600 litre filter cartridge
- DP10 Descaler powder



Technical Data

	EB3FX/TT
Width (mm)	250
Depth (mm)	525
Height (mm)	600
Height from tap to drip tray (mm)	250
Depth excluding drip tray	470
Number of taps	2
Output per hour (litres)	25
Rapid Draw-off (litres)	4.5
Heat up time to working temperature (full tank capacity)	31
Recovery per minute (litres)	0.40
Water inlet connection (BSP male)	¾"
Water inlet pressure (bar)	6
Total power rating (kW)	3
Standby power consumption (kW)	0.1
Electrical supply 1N~+E 230V 50-60Hz Current Rating (Amps)	13
Net weight empty (kg)	13
Net weight full (kg)	28
Packed weight (kg)	15
Shipping volume (m3)	0.152
IPX Protection	IPX3

