



## Wall Mounted Automatic Water Boiler

M3F, M5F, M7F

- High quality boiling water on tap 24 hours a day
- Wall mounted, compact design
- Easy installation – UK 3 pin plug and three screws
- Built-in water filtration system improves water quality
- High volume, easy change FilterFlow cartridge
- Adjustable water temperature – from 70°C – 96°C
- Precise electronic temperature control system
- LCD information panel
- Enhanced multi-level diagnostics



### Water Boiler Features

- High quality filtered boiling water on tap 24 hours a day
- LCD information panel
- Precise electronic temperature control system
- Insulated tank for minimal heat loss and energy conservation
- High volume, easy change FilterFlow cartridge - removes sediment and impurities such as chlorine
- Adjustable water temperature - from 70°C - 96°C
- Enhanced multi-level diagnostics
- Designed for connection to a potable cold water supply
- WRAS approval pending

### Cleaning and Servicing

- Easy clean stainless steel external finish
- Easy change filter cartridge

### Overall Construction

- Long life incoloy element
- Brushed finish stainless steel
- Stainless steel water tank
- 1.5 metre cable and a 13 amp moulded plug

### Inclusive Accessories

- Water feed hose (1m)
- FC04 5,600 litre filter cartridge
- Wall mounting bracket

### Available Options

### Available Accessories

- FC04 5,600 litre replacement filter cartridge
- DP10 Descaler powder
- DR94 M3F drip tray
- DR95 M5F & M7F drip tray



## Technical Data

|                                                               | M3F    | M5F    | M7F    |
|---------------------------------------------------------------|--------|--------|--------|
| Width (mm)                                                    | 300    | 340    | 340    |
| Depth (mm)                                                    | 203    | 203    | 203    |
| Depth (mm) inc tap                                            | 269    | 269    | 269    |
| Height (mm)                                                   | 398    | 448    | 563    |
| Output per hour (litres)                                      | 28     | 28     | 28     |
| Rapid Draw-off (litres)                                       | 3.5    | 5.5    | 8      |
| Heat up time to working temperature (full tank capacity)      | 8      | 12     | 18     |
| Water inlet connection (BSP male)                             | 3/4"   | 3/4"   | 3/4"   |
| Water inlet pressure (bar)                                    | 1 to 8 | 1 to 8 | 1 to 8 |
| Total power rating (kW)                                       | 3      | 3      | 3      |
| Standby power consumption (kW)                                | 0.6    | 0.6    | 0.6    |
| Electrical supply 1N~+E 230V 50-60Hz<br>Current Rating (Amps) | 13     | 13     | 13     |
| Net weight empty (kg)                                         | 8.9    | 9.9    | 11.6   |
| Net weight full (kg)                                          | 12.1   | 15.1   | 19.4   |
| IPX Protection                                                | IPX23  | IPX23  | IPX23  |

